


Grid Compatibility

The following chart shows the appropriate GRID TYPE for JLC-Tech grid lighting products for the specified ceiling.

Specified Grid Type →



15/16"
Flat Grid




9/16"
Flat Grid



9/16"
Bullnose
Grid



9/16"
Bolt Slot



15/16"
Flat Grid w/ Partially
Concealed Tiles



9/16"
XM Cross Tee for
Armstrong
DesignFlex™

Product Line	Compatible JLC-Tech Grid Type Ordering Code					
T-BAR LED	24	15	15	15B	24C	-
T-BAR LED X SERIES	24	15 or 15H	15 or 15H	15B or 15HB	24C	-
T-BAR ECO	24	15H	15H	15HB	-	-
T-BAR ECO DC	24	15H	15H	15HB	-	-
T-BAR FLEX	-	-	-	-	-	15
GEMINI	24	15	15	15B	-	-

How to Specify →

Grid Size*	Grid Type	Optic
2 = 2 ft	24 = 15/16	D = Diffusing Lens
4 = 4 ft	15 = 9/16	B = Block Clear Diffusing Lens
5 = 5 ft	15B = 9/16 Bolt Slot	B2 = Block Frosted Diffusing Lens
Metric	15H = 9/16 High Efficiency*	DW = Diffused White Lens
6 = 60 cm	15HB = 9/16" High Efficiency Bolt Slot*	
12 = 120 cm	24C = Partially Concealed	

Please reach out to our Customer Experience Team at 781-826-8161 or info@jlc-tech.com with any additional questions